

LLD1(JPK、JSB-KPP) Series Deviation switch 系列跑偏开关

用途 Application

LLD1(JPK、JSB-KPP)系列两极防偏开关安装在胶带输送机首尾端两侧，主要防止胶带跑偏事故。当胶带跑偏10°时发出报警信号，通知操作者要进行跑偏纠正，当胶带跑偏30°时，立即切断运行电路。实现安全保护。

LLD1(JPK、JSB-KPP) Series stage-two anti-deviating switch is used in tape conveyer by mounting on its two ends. It serves as the prevention of tape deviating. It can give the alarm when the tape deviates 10° with normal moving track. If 30°, it will cut off the circuit at once for safeguard purpose.

技术参数 Main technology data

型号 type	偏转角度 deviated angle	动作力矩 motion moment	额定容量 Rated capacity	触点数量 qty.of contact	复位方式 Resetting way	防护等级 protection degree
LLD1-S、Z JPK2-S、Z JPKJ-S、Z JSB-KPP-S、Z	30°	<5.5N.m	AC380V 3-5A	二开二闭 2open 2closed	S手动(manual) Z自动(automatic)	IP55

LLD1-S
JPK2-S
JPKJ-S
JSB-KPP-S

LLD1-Z
JPK2-Z
JPKJ-Z
JSB-KPP-Z

