

LLB3-63 Mini Circuit Breaker

Breaking capacity

Standard	Rated current(A)	Pole	Rated voltage(V)	Breaking capacity (A)	
BS3871-1	1 to 40	1	240	6000	
		2,3,4	415	6000	
	50 to 60	1	240	4000	
		2,3,4	415	4000	
	IEC157-1	1	1	220/240	10000
			2,3,4	220/240	20000
3		1	220/240	8000	
		2,3,4	380/415	10000	
BS3781-1		1 to 40	1	240	4000
			2,3,4	415	4000
	10 to 40	1	220/240	7000	
		2,3,4	220/240	16000	
	IEC157-1	50	1	220/240	6000
			2,3,4	380/410	8000
60		1	220/240	5000	
		2,3,4	380/410	6000	
BS3781-1		1 to 40	1	240	4000
			2,3,4	415	4000
	1 to 40	1	220/240	6000	
		2,3,4	220/240	12000	
	1 to 40	1	220/240	6000	
		2,3,4	380/415	6000	



LLB3-63/1P



LLB3-63/2P



LLB3-63/3P



LLB3-63/4P

Specifications

Rated temperature 40°C

Rated voltage 240V/415V AC

Rated current(C):1,3,5,6,10,15,16,20,25,32,40,50,60,63A
(D):1,3,5,6,10,15,16,20,25,32,40A

Electric endurance not lower than 6000 times

Mechanical endurance lower than 2000 times

Dimensions

