

General Relay

Main technical parameter

Specifications		Model	55.02	55.04	55.32
Terminal layout			2Z	4Z	2Z
Contact capacity	AC		10A 250V	5A 250V	5A 250V
	DC		10A 30V	5A 30V	5A 30V
Contact resistance(mΩ)			≤50mΩ	≤50mΩ	≤50mΩ
Insulation resistance(MΩ)			≥100MΩ	≥100MΩ	≥100MΩ
Dielectric strength	BOC		1000VAC	1000VAC	1000VAC
	BCC		1500VAC	1500VAC	1500VAC
Coil nominal voltage	AC		6 to 240V	6 to 240V	6 to 240V
	DC		6 to 110V	6 to 110V	6 to 110V
Coil nominal power	AC		0.9VA to 1.2VA	0.9VA to 1.2VA	0.9VA to 1.2VA
	DC		≤0.9W	≤0.9W	≤0.9W
Electrical life(OPS)			10 ⁵	10 ⁵	10 ⁵
Mechanical life(OPS)			10 ⁷	10 ⁷	10 ⁷
Operating temperature(°C)			-40~+60	-4~+60	-40~+60
Weight(g)			≤35	≤35	≤35
Mounting methods			Printed-circuit board, Flange, Outlet	Printed-circuit board, Flange, Outlet	Printed-circuit board, Flange, Outlet



55.02



55.04



55.32

Dimension

