

NT Series H.R.C Fuse Link & Base

NT type low voltage H.R.C. fuse features light in weight, small in size, low in power, loss and high in beaking capacity. This product has been widely used in overload and short circuit protection of electric installations.

This product conforms to IEC269 and VDE0636 standards of the rating at the world advanced level.

Specification



NT2 NT2 fuse link



NT3 NT3 fuse link



NT4 NT4 fuse link



NTB fuse handle

Type	Fuse link				Fuse base		
	Rated current (A)	Rated voltage (V)	Rated power loss(W)	Weight (kg)	Type	Rated current (A)	Weight (kg)
NT2	125	500 600	9	0.65	sist401	400	1.2
	160	500 600	11.5				
	200	500 600	15				
	224	500 600	16.6				
	250	500 600	18.4				
	300	500 600	21				
	315	500 600	19.2				
	355	500 600	24.5				
	400	500 600	26				

Type	Fuse link				Fuse base		
	Rated current (A)	Rated voltage (V)	Rated power loss(W)	Weight (kg)	Type	Rated current (A)	Weight (kg)
NT3	315	500 600	21.7	0.85	sist601	630	1.5
	355	500 600	22.7				
	400	500 600	26.8				
	425	500 600	28.9				
	500	500	32				

Type	Fuse link				Fuse base		
	Rated current (A)	Rated voltage (V)	Rated power loss(W)	Weight (kg)	Type	Rated current (A)	Weight (kg)
NT4	800	380	62	1.95	sist 1001	1000	3.45
	1000	380	75				